

2020

dupal^{UK}

LB SHOWER[®]

TECHNICAL
SPECIFICATION



LE SHOWER®



MATERIAL

White ABS impregnated with antibacterial additive.

Hose tube: White reinforced PVC with Antibacterial additive.

Hose fitting: ABS impregnated with antibacterial additive.



WORKING PRESSURE RANGE

0.5 bar – 5 bars



WORKING TEMPERATURE RANGE

Up to 75°C



FLOW RATE

8 litres per min at 2.5 bars.



APPROVALS

WRAS approval (Head and Hose)



FITTINGS

1/2" BSP female



PRODUCT MARKING

Dupal on the Shower Face (button)



COLOURS

Blue, Purple, Red and Green.
Order determined after customer consultation.



Colour Coded head and hose for easy inspection and replacing.

Design and Performance

Product was designed to be very robust, yet economical, and had zero failures to date. Head has been designed to be externally smooth with no dirt traps; the internal surface area is low reducing the area water comes into contact with following advice given by Infection Control experts. Head is not restricted or aerated but delivers a great shower using around 8 liters per min at 2.5 bar pressure and continues to work well down to 0.5 bar pressure. Dependent on previous usage quantities this can reduce water and energy costs while keeping great shower performance.



LB SHOWER®

dupal^{UK}



WRAS
APPROVED PRODUCT

01 342 844 844
sales@dupaluk.com
www.dupaluk.com

Dupal UK Limited
39 Careys Wood, Smmallfield
Surrey RH6 9PA, UK

VAT Number: 233 5070 38
Company Number: 09932632

